

AireTechnologies, Inc. 1502 Industrial Drive F Monographela PA 15063

phone: 866.421.AIRE fax 724.310.1262

www.airetechnologies.com



Job______ Location ______ Submitted to ______ Submittal Prepared by ______ Approve Date ______ Date _____

UL Classified - For use in installations rated 3 hours or less

22Ga. 1 piece rollformed frame

Standard fusible link - 165° (or w/optional 212°)

S

S

Φ

d

S

Standard Link attachment or Easy Access option

Ceramic Thermal Blanket provided on units with blade areas of greater than 80 sq. in.

Available in stainless steel

Available in sizes from 4" - 24" in standard link attachment and 5" - 24" in easy access link attachment.

CRD Series 55 SL & EA







55 SL

55 EA



ceiling dampers established by:

UL Standards 263 & 555C NFPA Standard 90A ICC Building Codes

Part Number Format



MODEL

55 SERIES - CRD, ROUND, 3 HOUR

METHOD OF LINK ATTACHMENT

SL - STANDARD LINK EA - EASY ACCESS LINK

DAMPER DIAMETER

MATERIAL & LINK TEMP.

G - GALVANIZED, W/165° LINK **H** - GALVANIZED, W/212° LINK **S** - STAINLESS STEEL, W/165° LINK **T** - STAINLESS STEEL, W/212° LINK





AireTechnologies, Inc. 1502 Industrial Drive E. Monongahela, PA 15063

phone: 866.421.AIRE fax 724.310.1262