



P: 800.961.7370
www.solerpalau-usa.com

GALVANIZED MOTORIZED DAMPER MODEL GMD

FEATURES

Frame

- 2" deep x 11/2" flanged x 14 gauge Galvanized Steel.

Blades

- 6" wide x 16 gauge Galvanized Steel. Parallel Blade Action.

Construction

- "MIG" welded frames.

Seals

- Stainless Steel Jamb Seals.

Tie Rod

- 11 gauge Galvanized Steel tie rods and blade clips. On-blade type.

Bushings

- Brass

Mounting Holes


- 9/32" x 1/2" slotted.

Finish

- Galvanized

Performance Criteria:

- 3,500 fpm Maximum Velocity.
- 4" wg Maximum Pressure.
- 122 Degree Maximum Temperature.



Note: Above dimensions* or - normal tolerance of .0625".

MOTOR SPECS

Motor Manufacturer	Model Number	Power Supply Required
Belimo	TF120-S	120/240 V 50/60 Hz
Motor Type	Temp. Range F°	
2 position Spring Return	-22 to 122	

Dimensions in Inches

Part No.	Overall (A & D) Frame Dimensions (W x H)	Inside (C & E) Frame Dimensions (W x H)	Required (B) Hole Opening (W x H)	Face Area (Sq. Ft.)	Est. Free Area (Sq. Ft.)	Est. Shipping Weight (lbs)
GMD12	15 x 15	12 x 12	13 x 13	1.00	.84	14
GMD16	19 x 19	16 x 16	17 x 17	1.78	1.67	21
GMD20	23 x 23	20 x 20	21 x 21	2.78	2.05	25
GMD24	27 x 27	24 x 24	25 x 25	4.00	3.59	32
GMD30	33 x 33	30 x 30	31 x 31	6.25	5.68	53
GMD36	39 x 39	36 x 36	37 x 37	9.00	8.25	67
GMD42	45 x 45	42 x 42	43 x 43	12.25	11.31	83
GMD48	51 x 51	48 x 48	49 x 49	16.00	14.84	98

Note: Dimensions are approximate due to normal tolerances in the manufacturing process. Estimated Free Area calculation is based upon the following formula: $MD[A+B+(N \times C)]/144$. Free Area x FPM = CFM; actual performance may vary.

